

## Informationen zum Produkt

## 600D



Füllvolumen:	Ø:	Höhe m.D.:	Gewicht Becher, Deckel (+/-3%)	IML-Druck Becher	IML- Druck Deckel	Weiteres:
600ml	109mm	103mm	23,13g / 6,9g	nein	nein	Siehe Spez.
<ul style="list-style-type: none"> <li>• PP-Spritzgussbecher mit Originalitätsverschluss (BRC-Zertifikat Lebensmittelsicherheit)</li> <li>• Standardausführung: klar mit klarem Deckel (Einfärbung in Standardfarben möglich)</li> <li>• Fertigung in Tiefkühlqualität zur Erhöhung der Schlagfähigkeit auf Anfrage (Eisindustrie)</li> </ul>						
Menge je Palette:	in 20 Kombiboxen paarig gep.	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Palette	Paletten- Höhe	Weiteres:
5.500 St.	275 St.	592x392x400mm  720g	28g	1200x800x150mm  23kg	Inkl. Pal.  2,20m	Siehe Spez.

## Standardfarben zur Einfärbung



**schwarz**



**rot**



**braun**



**weiss**



**orange**



**gelb**



**grün**



**blau**



**dunkelblau**

# Technical Data Sheet

## Container 600 ml Ø106, lid

<b>1. Dimensions</b>	Shape:	Round	
	Volume under lid:	600	ml
	External diameter top (with lid):	109,9	mm
	External diameter bottom:	85,3	mm
	Height (with lid):	103	mm
<b>2. Closure system</b>	Closure type:	Snap-On	
	Protective collar:	Yes	
	Tamper evident:	Yes	
	Lid type options:	Standard lid	
<b>3. Weight*</b>	Container:	23,13	g
	Lid:	6,90	g
	Handle:	2,46	g
	*the weight can have +/-3 % error		
<b>4. Handle</b>	Handle available:	Yes	
<b>5. Raw material</b>	Raw material:	PP	
	Masterbatch colours:	Standard colours or colours coordinated according to customer's presented colour pallet or sample.	
	Approvals:	All raw materials and masterbatches used in the production process have the appropriate food contact approvals.	
<b>6. Decoration</b>	IML decoration (container):	No	
	IML decoration (lid):	No	
<b>7. Other characteristic</b>	Uses:	Containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.	
	Hot filling:	Packaging is suitable for contact with the hot filling (85 °C - 95 °C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before approval for use at hot temperatures.	
	Cold temperatures:	Package made from the special cold-resistant material can be used at temperatures below -20 °C . It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before approval for use at low temperatures.	
	Storage:	Suitable storage include protection of direct sun light, rain, very high temperatures over a long period. Package must be not more than 2.4 m in height and at least 1 m away from the heat source. Recommended period of storage - 12 months after delivery to suitable storage.	
<b>8. Packing</b>	<b>Standard</b>		
	Containers per carton box	342	pcs.
	Lids per carton box	1600	pcs.
	Containers and lids packed together per carton box	275	pcs.
	Carton boxes per pallet	20	pcs.
	Containers per pallet	6840	pcs.
	Lids per pallet	32000	pcs.
	Containers and lids packed together per pallet	5500	pcs.
	Height including pallet	2,2	m
	<b>Optional</b>		
	Carton boxes per pallet	24	pcs.
	Containers per pallet	8208	pcs.
	Lids per pallet	38400	pcs.
	Containers and lids packed together per pallet	6600	pcs.
	Height including pallet	2,6	m

